

Premier Plus

Interlocking carpet entrance tiles to keep internal floor coverings clean and slip free



- Quality needlepunch carpet inserts available in two colours, which effectively scrape dirt and wipe moisture.
- Tiles simply clip together on site for ease of transportation and installation.
- Move, clean or replace individual tiles - they clip together with ease.
- Tiles offer flexibility in the size and shape which can be covered.
- Easily cut to shape, so you can fit to any space and install faster with fewer specialist tools.
- Fire tested to BS EN 13501-1 and slip tested to BS 7976-2.



Styles Available



Charcoal



Grey

Part Number	Size	Colour	Weight (kg)
PMP010101	29 cm x 44 cm	Charcoal	1.2
PMP010101C	30 cm x 45 cm	Charcoal	1.2
PMP010601	29 cm x 44 cm	Grey	1.2
PMP010601C	30 cm x 45 cm	Grey	1.2

Material	PP in PVC tile
Product Height	14 mm
Typical Applications	Entrance areas
Installation Method	Installed in to recessed well
Fire Tested to	BS EN 13501-1 Class Efl - s2
COO (Country of Origin)	UK
Guarantee	5 years
Slip Tested to	BS 7976-2 - low slip potential
Tile height	12.5 mm

Additional Information



Installation Guide



Installation Guide



Installation Guide



Premier Plus - BS 7676-2 Pendulum Slip Test



Premier Plus - EN ISO 11925 Fire Test



Installation Guide



Installation Guide



Installation Guide



Premier Plus - BS EN 13501 Fire Test



Premier Plus - EN ISO 9239 Fire Test

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)116 240 1088 or email sales@cobaeurope.com

www.cobaeurope.com